



DESCRIPTION

METHOD FOR TREATING OF OILS AND FATS

FIELD OF THE INVENTION

The present invention relates to a method for treatment of oils and fats, in particular, relates to a method for treatment of oils and fats characterized by making it possible to reuse ~~a-treated~~ wasted oils and fats or ~~a-treated~~ discharged oils and fats not depending on ~~containing ratio~~ the amount of saturated fatty acid·unsaturated fatty acid.

DESCRIPTION OF THE PRIOR ART

Presently, there are many sorts of wasted oils and fats in Japan. For example, tallow, bovine born oil, bovine internal organ oil ~~of bovine~~, lard, pig bone oil, pig internal organ oil ~~of pig~~, chicken oils and fats, residue oil formed at a refining process of animal oils and fats or vegetable oils and fats, animal foots oil or vegetable foots oil formed ~~at from~~ rendering ~~of~~ animal oils and fats or vegetable oils and fats, strong alkaline dark oil formed at a treating process of a foots oil, various wasted animal oils and fats or vegetable oils and fats discharged from a ~~feeds~~ food processing factory, waste oils and fats discharged from ~~producing a~~ production process of purified oil for ~~feeds~~ food as a by-product, for example, discharged oil generally called as "oil foots" at a producing process of beans oil, rapeseed oil or corn oil or waste foods oil such as waste oil from deep-fried food processing. ~~Now a days~~ Nowadays, it is said that the total amount of these waste ~~oil~~ oils ~~for~~ a year is more than 10 million tons or more than 20 million tons.

Further, from ~~a disturbance~~ the occurrence of mad cow disease, it became necessary to treat and burn up ~~bovine originated~~ bovine-originated oils and fats separately from other oils and fats. However, since ~~calori~~ the calories of ~~bovine-originated~~ bovine-originated oils and fats is high, the

durability of a burning furnace becomes ~~problem~~, a problem and safe burning ~~up~~ of it ~~can not~~ cannot be expected. Therefore, it ~~is obligated~~ was necessary to preserve waste ~~bovine~~ originated bovine-originated oils and fats separately until a treating method ~~is~~ was developed, however, actually, ~~bovine~~ originated bovine-originated oils and fats ~~is~~ are mixed with other oils and fats and ~~is~~ are not controlled as obligated. Therefore, a development of a new treating method is becoming a pressing subject.

Regarding animal oils and fats, ~~except bovine~~ originated for bovine-originated oils and fats, although a part of it is used as a fodder ~~effor~~ for a domestic animal, foods or cosmetic composition, ~~mainly mostly~~ is burned up. And, ~~regarding.~~ Regarding residue oil formed at a refining process of animal oils and fats or vegetable oils and fats for ~~feeds~~ food, since said residue oil is mainly ~~a~~ strong alkaline waste oils and fats, the durability of an ordinary furnace is a problem and, accordingly, ~~a~~ treatment by burning ~~up~~ is impossible.

A part of waste ~~feeds~~ food oil is used as a fuel ~~effor~~ for Diesel ~~engine~~ engines by converting by the "methylesterfication method". This method can be illustrated as follows. That is, methanol or ethanol and sodium hydroxide are mixed ~~to~~ with a waste ~~feeds~~ food oil with constant stirring, then the mixture is left ~~for standing~~ to stand. Glycerin or others, which are impurities, are absorbed by methanol or ethanol and ~~separated~~ separate to an upper side when ~~staying~~ maintained in a standing state. ~~And oil~~ Oil, which is located at a lower side, is used as a fuel. However, this method can only be applied for the refining of high quality waste ~~feeds~~ oil, food oil and cannot be applied for refining of middle quality waste ~~feeds~~ food oil, low quality ~~feeds~~ food oil or mud waste ~~foots~~ oil. The reason why can be illustrated as follows. That is, the "methylesterfication method" is a technique developed 50 or 60 years ago to convert a virgin oil such as soy bean oil or rapeseed oil to a ~~fuel,~~ fuel and ~~can not~~ cannot be applied to

~~ana~~ used waste ~~feeds~~food oil which is characterized in that the oxidation degree ~~ishas~~ progressed to a higher level. Therefore, middle quality waste ~~feeds~~food oil, low quality ~~feeds~~food oil or mud waste ~~foots~~ oil are omitted from the object of refining by this method. Further, oils and fats ~~efhaving~~ a high ~~containing~~ ratio of saturated fatty acid ~~is~~acids are out of the discussion. Furthermore, a method of "conversion of waste ~~feeds~~food oil, fish oil to Diesel engine fuel by ozone treatment, is also applied. This method is a technique objected to for oils and fats whose ~~containing~~ ratio of saturated fatty acid ~~is~~acids is high (for example, soy beans oil, rape seed oil, corn oil, camellia oil or fish oil).

~~Said~~This method is a technique ~~to pour~~of pouring materials to be treated (oils and fats characterized in that ~~contents~~the content of unsaturated fatty acid is high) into a reaction tank and ozone is added from a lower position of the reaction tank, ~~then~~when, the double bond of the unsaturated fatty acid ~~is~~acids is dissociated by oxidization ~~forth of~~ ~~ozone~~by ozone and thus converts the material to a fuel. Therefore, a waste oil whose ~~contents~~content of unsaturated fatty acid is high (high quality, middle quality, low quality and mud oil) can be refined by this method, however, oils and fats whose melting point is high and concentration of saturated fatty acid ~~is~~acids is high, such as palm oil, residue oil of palm oil, coconut oil or residue oil of coconut ~~oil~~oil, ~~cannot~~ be treated by this method. Further, said method ~~can not~~cannot be applied to a strong alkaline waste oil too. For example, in a case when oils and fats whose ~~contents~~content of saturated fatty acid ~~is~~acids is high is treated by this method, large amount of ozone is added to dissociate the double bonds of the fatty acid. ~~And when~~ ~~adding~~When the amount of ozone ~~become~~added becomes large and the time ~~to add~~of adding also becomes long, consequently, the saturated fatty acid ~~causes~~acids cause polymerizing ~~reaction~~reactions by the ozone reaction. ~~Said~~The polymerizing

~~reaction means the~~ reactions mean a state that the oils and fats ~~eauses~~ cause caking.

Oils and fats can be roughly classified ~~to ainto~~ saturated fatty acid acids and unsaturated fatty acid acids. When the content of saturated fatty acid acids becomes large, the melting point and caking ratio become high and ~~solidified~~ solidification occurs quickly. As oils and fats whose content of saturated fatty acid acids is larger than 80%, tallow (Fedd oil), bovine born oil, pig oil (lard), pig bone oil, chicken oil, sheep oil, goat oil or horse oil can be mentioned. ~~And as~~ As a vegetable oil, palm oil, residue oil of palm oil, coconut oil and residue oil of coconut oil can be mentioned.

As oils and fats which ~~contains~~ contain more than 80% of unsaturated fatty acid acids, soy ~~beans~~ bean oil, rape seed oil, sunflower oil or corn oil can be mentioned as a vegetable oil, and fish oil can be mentioned as an animal oil.

Because unsaturated fatty acid acids can be more easily treated than saturated fatty acid acids, the development has ~~been progressed~~ on oils and fats whose content of unsaturated fatty acid acids is high.

SUMMARY OF THE INVENTION

The present invention relates to a treating method of oils and fats and the object of the present invention is to provide a material for various oils and fats, such as a fuel, by treating oils and fats whose ~~contents~~ content of saturated fatty acid acids is high.

The gist of the present invention is a treating method of oils and fats ~~characterizing to carry~~ characterized in carrying out ozone ~~treatment~~ and light irradiation ~~treatment~~ treatments on oils and fats ~~of in~~ in a state ~~of just prior to~~ hydrolysis.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a flow sheet illustrating ~~processes~~ a process of the present invention, Figs. 2 and 3 are

~~illustrating~~illustrate views of a treatment apparatus of the present invention. Fig._4 is an illustration view of a light irradiation apparatus of the present invention, Fig._5 is an illustration view of another example of a treatment apparatus of the present invention. ~~Marks~~The numerals in the drawing are ~~illustrated~~ as follows.

1. Material tank, 2. First pre-treatment tank,
3. Second pre-treatment tank, 4. Pre-filtration filter press,
5. Pre-coating tank, 6. Oil separator, 7. Special ray
irradiation device, 8. First treating tank, 9. Cooling
chiller, 10. Second filtration device, 11. Pre-coating tank,
12. Second treating tank, 13. Third filtration device,
14. Pre-coating tank, 15. Regulating tank,
16. Cartridge tank, 17. Vapor generating device,
18. Ozone generating device, 19. Ozone inserting opening,
20. Material gas pipe, 21. First tank (liquidizing tank),
22. Second tank (liquid recovering tank), 23. Filtration
device, 24. Liquefied gas fuel tank, 25. Stirrer
26. Filter, 27. Lubricating oil recovering device

DESCRIPTION OF THE PREFERRED ~~EMBODIMENT~~EMBODIMENT

The present invention will now be illustrated in more ~~in~~ detail.

Regarding waste oils and fats and discharged oils and fats which can be treated by the present invention, it is possible to ~~be treated not~~treat them without considering ~~at~~the containing ratio of saturated fatty ~~acid~~acids·unsaturated fatty ~~acid~~acids. Waste oils and fats of the present invention means oils and fats which ~~is~~are treated by alkali or refined during a rendering process, however, also not treated oils and fats can also be treated. Specifically, animal ~~oil~~oils such as tallow (Fedd oil), bovine bone oil, pig oil (lard), pig bone oil, chicken oil, sheep oil, goat oil, horse oil or fish oil or a vegetable oil such as palm oil, residue oil of palm oil, coconut oil and residue oil of coconut oil, soy ~~beans~~bean oil, rape seed oil, sunflower oil or corn oil can be mentioned.

Further, regarding an ozone treatment, since the double bond or triple bonds of saturated fatty acid or unsaturated fatty acid ~~becomes~~ acids become easy to dissociate by light, ozone is ~~inserted~~ injected from a lower part of each treating reaction ~~tank,~~ tank and specific treatment is performed on an ozone ~~inserting~~ injection opening so as ~~to progress~~ that the ozone reaction progresses smoothly. ~~Said~~ The specific treatment means that a metallic net having 0.5 μ m to 1 μ m openings is ~~equipped~~ provided in a pipe of ~~ozone inserting~~ an ozone-injection opening. By ~~equipping~~ providing said fine metallic net, the ozone is divided ~~to~~ into ultra fine bubbles and the reaction can be progressed progress smoothly.

These waste oils and fats or discharged oils and fats (shortened to simply oils) should be set to a state of just prior to hydrolysis. For the purpose ~~to set to~~ of setting the state of just prior to hydrolysis, it is necessary to add moisture (vapor) to the oils and to carry out heat treatment and ~~is desirable to press by~~ use a pressure of 3-10 ~~atmos~~ aiming at atmospheres to shorten the treating time. By setting to a state of just prior to hydrolysis, stable saturated fatty acid ~~becomes~~ to acids become easier ~~reactionable state~~ to react by light irradiation and ~~by~~ ozone treatment.

Ozone treatment and light irradiation treatment are carried out on the oils ~~set to~~ which are at a state of just prior to hydrolysis. Either ozone treatment or light irradiation treatment can be carried out first. Regarding the light irradiation treatment, it is desirable to change the wave-length of the light to be irradiated according to a ~~set~~ the type of the oil oil, for example, in a case ~~to produce~~ of producing Diesel engine fuel from tallow, a desirable wave-length of light is 155nm to 325nm, which belongs to the domain of ~~ultra-violet,~~ further ultraviolet. Further, according to the power of a ray ray-generating source, light of 185nm to 256nm can be used. Furthermore, in a case ~~to produce~~ of producing an oil which does not solidify at approximately 0°C, which is used in ~~feeds~~ food processing or

cosmetic composition processing, it is possible to cause a cleavage reaction and ~~to produce~~ an oil which does not solidify at approximately 0°C by combining ~~ultra violet~~ultraviolet light, visible light and ~~infra-red~~infra-red light of 356nm-405nm-800nm.

EXAMPLE

Example 1

As an Example of the present invention, ~~at the~~ flow sheet of Fig. 1, which relates to a process ~~to produce of~~ producing Diesel engine fuel from tallow, will be illustrated. Figs. 2 and 3 illustrate ~~an~~ equipment of the present invention and, however, ~~is are~~ not ~~intending~~intended to restrict the scope of claims of the present invention.

(a) Material is supplied to a material tank (1) of approximately 20L capacity. Various ~~sorts~~soils can be ~~mentioned~~used as ~~at the~~ material, and the material is heated in the material tank according to the purpose of the treatment. ~~Material~~The material is regulated by adding 3-5% of water to the total amount of the material if necessary.

(b) The regulated oil is transferred to a first pre-treatment tank (2). The first pre-treatment tank (2) has a capacity of approximately 20L, which is the same volume ~~to as~~ the material tank. Since the purpose is to produce Diesel engine fuel from tallow, 3-8% of vapor to the total amount of the material is blown from the lower part of the tank so as to ~~program~~control the temperature to 120°C-130°C, and ozone, which is generated from an ozone generating device (18), is introduced from the lower part of the tank. This pre-treatment reacting apparatus is ~~pressed by~~ at a pressure of 1-2 ~~atms~~atmospheres and stirred well. The material is reacted to a state of just prior to hydrolysis. For the purpose ~~to shorten of~~ shortening the treating time, it is possible to ~~press~~pressurize the apparatus to 3-10 ~~atms~~atmospheres. Further, this reacting apparatus is heated to 150°C-250°C and 5-8% or 10% of vapor to the total amount of the material is added and ozone is introduced. After

this process, said reacting apparatus is ~~vacuumed to~~put under a vacuum of minus 2-3 or 5 ~~atmospheres~~ and vapor (water) used in the previous process is removed. Thus, the material is reacted to a state of just prior to hydrolysis.

(c) Then the material, which is in a state of just prior to hydrolysis in the first pre-treatment tank, is poured into a second pre-treatment tank (3). To the material poured into the second pre-treatment tank (3), a stirrer which can pulverize the material to ultra fine particles and stir it ~~by~~at a rotating speed of 300-400 r.p.m. The stirrer, which can pulverize the material to ultra fine particles, of the present invention is characterized in that a stainless steel wire ~~brush~~brush is equipped at a pointed end of the stirrer or using a propeller processed to have ~~sawteeth~~sawtooth shape.

By providing a heater ~~equipped to~~with the equipment of the present invention, ~~humidity~~humidity (vapor) which ~~can~~not be removed by a vacuum process is removed by heating. ~~Said~~The heating is carried out at the temperature of 95°C-100°C or 100°C-120°C. ~~Impurity is~~Impurities are extracted from the material oil, which is ~~staying in~~in a state of just prior to hydrolysis. For the purpose ~~to remove~~of removing impurities, the material oil ~~is passed~~passes through a first filtration ~~device~~device and, during said process, ozone is added from the lower part of the equipment. During the process ~~to add~~of adding ozone and to promote oxidization, for the purpose ~~to express~~of suppressing excess oxidization, 1-2% of sawdust or woody tips to the total amount of the material ~~are~~is added.

(d) First filtration device: Material which has passed through the second pre-treatment process ~~is passed~~passes through the first filtration device for the purpose ~~to remove impurity~~of removing impurities extracted in the second pre-treatment process, such as glycerin or an absorbing agent added ~~at~~to the process, such as woody tips ~~added at the process~~, are removed. The first filtration device ~~is consisting~~consists of a pre-filtration filter press (4), a filtering cloth of the pre-

filtration filter press (4) is coated with an absorbing agent such as activated clay, diatomaceous earth, zeolite or activated carbon. Accordingly, impurities formed ~~at~~in the second pre-treatment device ~~is~~are absorbed and removed. The amount of the absorbing agent is 1-3% to the total amount of the material or, according to ~~a set~~the type of material, 2-6% to the total amount of the material.

(e) Oil separator: The purpose of an oil separator is to remove ~~humid more perfectly~~humidity remaining ~~at~~from the previous vacuum dehydration process. That is, material contained in the second pre-treatment device is ~~filtrated~~filtered by the first filtration device and ~~flows~~sent to the oil separator (6). The oil separator ~~is aiming to remove~~removes emulsified water remaining in the second pre-treatment device. ~~Said~~The emulsified water ~~is originated~~originates from ~~humid~~humidity (vapor) that is used in the material tank and in the first pre-treatment device and is not removed by the second pre-treatment device.

~~Shape~~The shape of the oil separator is cylindrical. Material is poured into the cylinder and discharged to the outside of the cylinder. This cylinder is specifically processed. Namely, the diameter of holes to pass through ~~is becoming~~become larger from an inner side toward an outer side. ~~Diameter~~The diameter of ~~hole~~the holes of the innermost side is 1 μ m and the diameter of ~~hole~~the holes of the outermost side is from 20 μ m to 30 μ m and, ~~and~~ by enlarging the size of the fine particles (clusters) of emulsified material (oil·water), oil and water is instantly separated when discharged ~~to the~~ outside of the cylinder.

Separated oil ~~is progressed~~progresses to the next process. ~~And~~ and separated water is transferred to a vapor generating device for the purpose ~~to of~~of reuse after ~~filtrated~~being filtered by activated carbon.

(f) Special ray irradiation device: Material (oil), after water is separated, ~~is flows~~sent into a special ray irradiation device (7). ~~In a case to produce~~When producing

Diesel engine fuel from tallow, the wavelength of the light to be used in the present invention is a wavelength of ultra violetthe ultraviolet domain of 155nm-325nm, ~~further.~~

Further, according to the power of a the ray generating source, light of 185nm to 256nm can be used. ~~In a case to use~~ When using oils and fats whose containing ratio of saturated fatty acid is high ~~to the~~ for a use exceptingexcept for fuel, for example, to produce an oil which does not solidifyingsolidify at approximately 0°C, which is used in ~~feedsfood~~ processing or cosmetic compounds processing, it is possible to cause a cleavage reaction and to produce said oil which does not solidify at approximately 0°C by combining ~~ultra violetultraviolet~~ light, visible light and ~~infra-redinfrared~~ light of 356nm-405nm-800nm.

As a method for irradiation, a spiral wire of glass or silicone is wound around a ray source tube, and the material ~~is flown~~ flows along with the spiral wire from the upper side to the lower side so as to irradiate light. One example is shown in Fig. 4.

As the other method for irradiation, a method ~~to irradiate~~ of irradiating by spraying the material in state of a mist or fog, a dipping method, or a wet wall method can be used. Namely, it is important to expand the irradiation area.

~~From~~ For the next step, the process is illustrated according to Fig. 3.

(g) First treating apparatus: ~~In the case of fuel~~ When producing fuel, the material after the process by a special ray irradiation device (7) indicates an igniting feature at this stage. ~~And in the case of~~ As for oils exceptingnot for fuel, the material after said process ~~becomes~~ does not ~~to~~ solidify at approximately 0°C. In the case of fuel producing, the purpose of the first treating tank (8) is to improve the quality as fuel, and in the case of oils ~~exceptingnot for~~ fuel, the purpose of the treatment is to enhance the value. To the transported material, 1-2% of rice-bran to the total amount of the material is added. ~~Oil~~ An oil washing process by

rice-bran is carried out and, simultaneously, ozone is ~~inserted~~injected through an ozone inserting opening so as to carry out an ozone reaction. (18) is an ozone generating device.

(h) Second filtration device: ~~Inside~~The inside of the second filtration device (10) is coated by ~~one~~a cake layer selected from the group consisting of activated clay, diatomaceous earth, zeolite or activated carbon, which is transported from a pre-coating tank (11). By this cake layer, rice-bran added during the first treating process by 1-2% to the total amount of the material is removed and the quality of the oils is improved.

(i) Second treating apparatus: Material after ~~passed~~passing through the second filtration device (10) is transferred to a second treating tank (12). ~~Object~~The object of this tank is to improve the oils containing a high amount of a saturated fatty acid whose melting point is high, such as an animal oil, palm oil or vegetable oil not to solidify at ~~the~~a temperature lower than 0°C. ~~Material~~The material is cooled down by a cooling chiller ~~equipped to~~provided at the inside of the tank according to the purpose. ~~Chilling~~The chilling temperature and the effect by chilling are as follows.

Material which has passed through each refining process is transported to a second treating tank and a second filtering device. When the material treated in the second treating tank is cooled down to 5°C by a cooling chiller, then passed through the second filtering device, the filtrated material does not solidify at ~~the~~a temperature of from -7°C to -15°C in a refrigerator.

Material is cooled down to 10°C → does not solidify up to -5°C to -7°C.

Material is cooled down to 5°C → does not solidify up to -7°C to -15°C.

Material is cooled down from 0°C to 1°C → does not solidify up to -20°C to -30°C.

(j) Third filtration device: Inside of a third filtration device (13) is coated by ~~one~~a cake layer selected from the group consisting of activated clay, diatomaceous earth, zeolite or activated carbon, which is transported from a pre-coating tank (14). Material after being treated by the second treating apparatus (12) ~~is passed~~passes through a cake layer of the third filtering device (13) ~~and filtered~~is filtered and introduced to ~~an~~a regulating tank (15). Then the material ~~is passed~~passes through a cartridge tank and an aimed product is produced.

~~Physical~~The physical properties of the product obtained by conversion of tallow (Fedd oil) to Diesel engine fuel is summarized in Table 1 in comparison with a methylesterfication method and light oil on the market.

Table 1

	Tallow after treated	Methylesterfication method	Light oil
Calorific value Cal/kg	10.733	9500	10920
Density (15°C) g/cm ³	0.888	0.888-0.90	0.835
Dynamic viscosity mm ² /S	8	8-9	5-6
Flash point °C	37	130-140	66
Fluidizing point °C	-7.5	Max -5	-8
Sulfur contents %	0.0016	0.01	<0.2

Pig oil (lard oil) whose solidifying point (freezing point) is +30°C is refined by ~~above the above-~~the above-mentioned apparatus and, ~~and~~ as a result, a liquid oil whose freezing point is -5°C is obtained.

Example 2

In this Example, a method ~~to obtain~~ of obtaining lubricating oil or fuel to be used instead of gasoline will be illustrated based on Fig. 5.

~~Same~~ The same as ~~to~~ with Example 1, according to the process shown in Fig. 2, (f) material after light irradiation treatment by a special ray irradiation device is transported to a first treating device (8). (~~in Fig. 2, as far as~~ In Fig. 2, a special ray irradiation device (7) is ~~at~~ the same apparatus.)

1) Material after the ray irradiation treatment is transferred to a first treating tank (8). After being transferred, 3-10% of a ~~gas-gas~~ gas-inducing agent to the total amount of the material is added to the material and stirred well.

~~Rotating~~ The rotating speed of a ~~stir~~ the stirrer is approximately 300 r.p.m. As a ~~gas-inducing~~ gas-inducing agent, hexane-~~ete~~ , etc., can be used.

As the result of the light irradiation, ~~hydro~~ carbon hydrocarbon oil is formed ~~by~~ in a 20-30% ratio in the transferred material.

~~To~~ At the inside of the first treating apparatus, a specially processed ozone inserting opening (19) is ~~equipped,~~ provided and from this opening, fine bubbles of ozone of 0.1 μ m-05 μ m size are blown in strongly and the blown in ozone ~~emulsify~~ emulsifies the material instantly. From the emulsified material, hydrocarbon gas ~~of hydro-carbons~~ is formed. The formed gas is transferred to a gas recovering apparatus mentioned below and liquefied. The liquefied product is almost the same as ~~to~~ gasoline of a high octane value. ~~Recovering~~ The recovering ratio from the material is ~~40-50%, 40-~~ 50% and 50-60% of the residue is lubricating oil.

Gas recovering apparatus

The gas recovering apparatus is composed of first tank (21), second tank (22) and a filtration device (23). First tank liquidates gas discharged from the first treating apparatus through a pipe (20) and second tank acts as a

recovering part of liquefied liquid. Functions can be illustrated as follows.

- (a) Gas discharged from the pipe (20) is introduced into a spiral pipe formed ~~in~~ inside of the first tank (21).
- (b) A proper quantity of water is contained in the first tank (21), said water is kept at 0°C and by quenching, the gas is liquefied.
- (c) Aiming at smooth liquidation of the gas, a vacuum pump is equipped ~~to~~with the second tank (22) (recovering part) and ~~operate the vacuum pump operated~~ to improve the recovering effect.

For the purpose ~~to improve~~of improving the quality, the recovered liquid is ~~filtrated~~filtered by a filtration device (23). As a method for filtration, filtration by a filter press, vacuum filtration or spontaneous filtration can be mentioned. As a filter, activated carbon, activated clay or zeolite can be used. The ~~filtrated~~filtered liquefied gas fuel is preserved in a liquefied gas fuel tank (24).

Material remaining in the first treating apparatus causes a polymerization reaction by the effect of fine particles of ozone regulated to 2-5µm size discharged from an ozone ~~inserting~~injecting opening (19) ~~equipped to~~provided at the lower part of the apparatus. ~~Expecting~~To more rapidly and accurately cause the polymerization reaction, stirring is carried out. ~~Desirable~~A desirable rotating speed is 10000-30000 r.p.m. However, if a ~~stir test~~stirrer at the end of a rotating axis of which a special processed stirrer (25) is ~~equipped~~provided, the rotating speed can be 300-360 r.p.m. ~~As a~~The stirrer (25), is not restricted, however, when a stirrer characterizing by a wire ~~brush~~brush of 0.1-0.3mm size is equipped at a pointed end of the rotating axis ~~forming~~having a cross shape or a stirrer using a propeller processed to have ~~sawteeth~~a sawtooth shape is used, a remarkable effect can be obtained.

~~Filtration~~The filtration process is ~~set~~for the purpose ~~to improve~~of improving the quality of the polymerized

material. ~~Filtrating~~The filtrating operation is carried out the same as to above the above-mentioned gas recovering process. That is, a filtering device (26) can be a filter press, vacuum filtration or spontaneous filtration and, as a filter, activated carbon, activated clay or zeolite can be used. ~~Polymerized~~The polymerized material, after the filtration process, is recovered at a lubricating oil recovering device (27).

From this treated material, a lubricating oil of a hardness of 10w-30~10w-40 for a gasoline engine or for a Diesel engine can be produced.

APPLICABILITY FOR INDUSTRIAL USE

By the treating method of the present invention, oils and fats whose content of saturated fatty acid, which is recognized to be hard to refine, can be refined by a simple refining method and can be provided as a material for various oils and fats. That is, this method is suited to a treating method of oils and fats whose content of stable saturated fatty ~~acid~~acids, waste oils and fats or, in particular, waste oils and fats ~~originated~~linked to mad cow disease, and is useful ~~to produce~~for producing Diesel engine fuel, lubricating oil or fuel and can be used instead of gasoline.